

Mancino 502

- A. Basis-of-Design Product: Subject to compliance with requirements. Provide Mancino Manufacturing Company model 502.
- B. Removable safety wall padding manufactured in 2-in-thickness, standard 2-ftaccordion style fold construction: Each mat is sewn with loop attachment along horizontal edge for connection to YKK® engineered wall hook and rail system. Covering is a 16 -oz. / yd2 vinyl coated polyester. Filler is firm crosslinked polyethylene foam.
 - Foam Filler: Total not less than 2-inch- (50.8-mm-) thick foam 2-lb/ ft3 (32-kg/ m3) density. Meets ASTM standard 2440-04 Impact attenuation where the panel has achieved ratings below 1000 HIC and 200 g max.
 - Vinyl Covering: 16 -oz. / yd2 (543-g/ m3) Vinyl Coated Polyester puncture and tear-resistant. CPSC CPSIA - 6P and lead compliant. Phthalates less than .1% and Lead less than 100 ppm. Achieving NFPA-701 CSFM, and a Class "A" fire rating under ASTM E-84, with a "smoke developed" index of 450 or less and a "flame spread" index of 25 or less. UV and Anti-Mildew treated.
- C. Sizing: Standard fold every 24-inches- in lengths of 4-ft-, 6-ft-, 8-ft-, or 10-ft-. *Combination of lengths and heights may be required to complete area.
- D. Color(s) of vinyl to be selected from manufactures standard color packet
- E. Installation: Comply with manufacturers written instructions, Refer to Architects elevation drawings for mat placement. Mount mat bottom even with finished floor. Install removable stage padding after painting and electrical has been completed.
 - 1. YKK® engineered wall hook and rail system mounts directly to stage top lying flat and running along stage edge
- F. Adjusting:
 - 1. Final adjustment of panels to insure a smooth finished appearance
 - 2. Clean and remove any debris from the working area
 - 3. Spot clean panels as may be necessary